

719 Series


Best in Class Double Liner Stencil

The 719 Series is a double liner stencil with a clear polyester outer liner and a yellow middle liner. It is designed for use with stone and other smooth surfaces.

Available for friction feed plotters, slot fed and tractor fed machines.



Friction Fed (719 Y)



Slot Fed, Gerber (719 YPS*)



Tractor Fed, IBM (719 YPT)

*Only 15 and 30 inch wide rolls are available for 719 YPS models.

Standard widths

12.75"	15"	18.75"	25"
27.75"	30"	32.75"	

Nominal values

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Adhesive	Regular
Total Thickness (mil)	47 (1.20 mm)
Tensile Strength (lbs/in)	5.7 (25.90 N/25 mm)
180° Adhesion to Steel (oz/in)	42 (11.89 N/25 mm)
Elongation (% at break)	390
Liners	Clear PET outside liner with yellow PET middle liner

Storage and shelf life

Store new stock behind current stock, in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F and 40% to 50% relative humidity are recommended.

Shelf life is 12 months from date of manufacture.

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

www.ublaststencil.com

Phone
706-283-2289
706-283-2280

Toll-free
1-855-590-7070

Fax
706-283-2290

Address
1039 Crosstie Drive,
Elberton, GA 30635

Email
info@ublaststencil.com

