


Technical Product Sheet

721 Series

Aggressive Single Liner for Stone

The 721 Series is designed for use in sandblasting with rough stone and other materials such as raw hardwood or brick. The single liner with clear mylar backing has aggressive adhesion with no need for filler.

Available for friction feed plotters, slot fed and tractor fed machines.



Standard Widths

15" 30"

Nominal Values

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Adhesive	High tack/Acrylic
Total Thickness (mil)	42 (1.07 mm)
Tensile Strength (lbs/in)	5.7 (25.90 N/25 mm)
180° Adhesion to Steel (oz/in)	46 (13.01 N/25 mm)
Elongation (% at break)	380
Liners	Clear PET outside liner

Storage and Shelf Life

Store new stock behind current stock, in a clean, dry place. Temperature of 70°F (21°C) +/-6°F and 40% to 50% relative humidity are recommended.

Shelf life is 12 months from date of manufacture.

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

www.ublaststencil.com



Toll-free 1-855-590-7070

Fax **706-283-2290**



