


723 Series

High-Tack Single Liner Stencil

The 723 Series is highly flexible and impact resistant with high-tack adhesive for smooth or uneven surfaces. The single liner with clear mylar backing does not contain PVC and is safe for laser cutting.

Available for friction feed plotters.



Standard Widths

15"	25"	30"
-----	-----	-----

Nominal Values

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Adhesive	High tack/Acrylic
Total Thickness (mil)	30 (0.762 mm)
Tensile Strength (lbs/in)	5.0 (22.72 N/25 mm)
180° Adhesion to Steel (oz/in)	46 (13.01 N/25 mm)
Elongation (% at break)	450
Liners	Clear PET outside liner

Storage and Shelf Life

Store new stock behind current stock, in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F and 40% to 50% relative humidity are recommended.

Shelf life is 12 months from date of manufacture.

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

www.ublaststencil.com

Phone
706-283-2289
706-283-2280

Toll-free
1-855-590-7070

Fax
706-283-2290

Address
**1039 Crosstie Drive,
Elberton, GA 30635**

Email
info@ublaststencil.com

