

ST380

Strip Tape that Protects

The ST380 Strip Tape is designed with high tack acrylic adhesive. This product is malleable and holds strong. The easy-cut and easy-release clear mylar liner is designed to protect surfaces for shot peening and PMB applications.



Standard widths

1"	2"	3"	4"
6"	12.5"	25"	30"

Nominal values

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Adhesive	High Tack/Acrylic
Total Thickness (mil)	47 (1.20 mm)
Tensile Strength (lbs/in)	5.7 (25.90 N/25 mm)
180° Adhesion to Steel (oz/in)	46 (13.01 N/25 mm)
Elongation (% at break)	420
Liners	Clear PET outside liner

Storage and shelf life

Store new stock behind current stock, in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F and 40% to 50% relative humidity are recommended.

Shelf life is 12 months from date of manufacture.

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

www.ublaststencil.com

C Phone
706-283-2289

706-283-2280

Toll-free **1-855-590-7070**

Fax **706-283-2290** O Address

1039 Crosstie Drive, Elberton, GA 30635 Email info@ublaststencil.com

info@ublaststend